

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS Reference Number: 160-SDS-ENG-029
Issue date: 3/8/2022 Revision date: 11/8/2024 Supersedes version of: 3/8/2022 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Industrial use
Use of the substance/mixture : Industrial use

1.3. Details of the supplier of the safety data sheet

Kastamonu Entegre Ağaç Sanayi ve Ticaret Anonim Şirketi
Altunizade Mahallesi Kısıklı Cad.No:13
34662
Üsküdar / İstanbul Türkiye
T +90 216 554 30 00
info@keas.com.tr, www.keas.com.tr

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains hexamethylene diacrylate; hexane-1,6-diol diacrylate (13048-33-4). May produce an allergic reaction.
EUH210 - Safety data sheet available on request.
Extra phrases : Restricted to professional users.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Comments : Contains wood fibers or chips, solid resin, water etc.

Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Modified Paraffin	CAS-No.: 8002-74-2 EC-No.: 232-315-6	0.3 – 2	Not classified
hexamethylene diacrylate; hexane-1,6-diol diacrylate	CAS-No.: 13048-33-4 EC-No.: 235-921-9 EC Index-No.: 607-109-00-8	0.1 – 2	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317
Benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1)	CAS-No.: 54553-90-1 EC-No.: 259-224-4	0.1 – 2	Aquatic Chronic 3, H412
formaldehyde ...% (Note B)(Note D)	CAS-No.: 50-00-0 EC-No.: 200-001-8 EC Index-No.: 605-001-00-5	< 0.01	Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Inhalation), H331 (ATE=0.5 mg/l/4h) Skin Corr. 1B, H314 Skin Sens. 1, H317 Carc. 1B, H350 Muta. 2, H341

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
formaldehyde ...%	CAS-No.: 50-00-0 EC-No.: 200-001-8 EC Index-No.: 605-001-00-5	(0.2 ≤ C ≤ 100) Skin Sens. 1; H317 (5 ≤ C < 25) Skin Irrit. 2; H315 (5 ≤ C < 25) Eye Irrit. 2; H319 (5 ≤ C ≤ 100) STOT SE 3; H335 (25 ≤ C ≤ 100) Skin Corr. 1B; H314

Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).
Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

- Reactivity in case of fire : At high temperature may liberate dangerous gases.
Hazardous decomposition products in case of fire : On heating or during combustion : Toxic fumes may be released.

5.3. Advice for firefighters

- Precautionary measures fire : Keep away from combustible materials. Keep container closed when not in use. Approach from upwind.
Firefighting instructions : Exercise caution when fighting any chemical fire. Keep upwind. Do not enter fire area without proper protective equipment, including respiratory protection. Eliminate all ignition sources if safe to do so. Contain the extinguishing fluids by bunding.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : Do not allow run-off from fire fighting to enter drains or water courses. Notify authorities if product enters sewers or public waters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Keep public away from danger area.

For non-emergency personnel

- Protective equipment : For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Ventilate spillage area.

For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Equip cleanup crew with proper protection. Evacuate unnecessary personnel.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product. Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep cool.
Incompatible products : Strong acids. Strong bases. Strong oxidizing agents.
Incompatible materials : Extremely high or low temperatures.

Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Germany

Storage class (LGK, TRGS 510)

Joint storage table

: LGK 13 - Non-combustible solids

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

Joint storage with restrictions permitted for

Joint storage permitted for

: LGK 1, LGK 6.2, LGK 7

: LGK 4.1A, LGK 5.1C

: LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 4.3, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

7.3. Specific end use(s)

See Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

formaldehyde ...% (50-00-0)	
EU - Binding Occupational Exposure Limit (BOEL)	
Local name	Formaldehyde
BOEL TWA	0.37 mg/m ³ 0.62 mg/m ³ (Limit value for the health care, funeral and embalming sectors until 11 July 2024) 0.3 ppm 0.5 ppm (Limit value for the health care, funeral and embalming sectors until 11 July 2024)
BOEL STEL	0.74 mg/m ³ 0.6 ppm
Notes	Dermal sensitisation (The substance can cause sensitisation of the skin)
Regulatory reference	DIRECTIVE (EU) 2019/983 (amending Directive 2004/37/EC)

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Protective clothing. Gas mask. Gloves. Safety glasses.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Not required for normal conditions of use

Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin protection

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Hand protection:

Does not require any particular or specific measures. Respect the general rules for occupational hygiene

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: According to product specification.
Appearance	: Solid.
Odour	: Wood. Slight.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not applicable
Boiling point	: Not available
Flammability	: Non flammable.
Lower explosion limit	: Not applicable
Upper explosion limit	: Not applicable
Flash point	: 204 – 260 °C
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not available
pH	: Not available
pH solution	: Not available
Viscosity, kinematic	: Not applicable
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not applicable
Particle size	: Not available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Modified Paraffin (8002-74-2)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

hexamethylene diacrylate; hexane-1,6-diol diacrylate (13048-33-4)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rabbit	3650 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) (54553-90-1)

LD50 oral rat	7400 mg/kg bodyweight Animal: rat, Guideline: other:
---------------	--

formaldehyde ...% (50-00-0)

LD50 dermal rabbit	270 mg/kg (Rabbit)
LC50 Inhalation - Rat [ppm]	< 463 ppm (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male/female, Experimental value)

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)

formaldehyde ...% (50-00-0)

pH	2.8 – 4
----	---------

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met)

formaldehyde ...% (50-00-0)

pH	2.8 – 4
----	---------

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

formaldehyde ...% (50-00-0)

IARC group	1 - Carcinogenic to humans
------------	----------------------------

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Modified Paraffin (8002-74-2)	
NOAEL (dermal, rat/rabbit, 90 days)	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
hexamethylene diacrylate; hexane-1,6-diol diacrylate (13048-33-4)	
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)	
Viscosity, kinematic	Not applicable

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met)

hexamethylene diacrylate; hexane-1,6-diol diacrylate (13048-33-4)	
LC50 - Fish [1]	0.38 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	2.7 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1.09 mg/l Test organisms (species): other:
EC50 72h - Algae [2]	2.33 mg/l Test organisms (species): other:
LOEC (chronic)	0.24 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.14 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.0723 mg/l Test organisms (species): Oryzias latipes Duration: '39 d'
Benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) (54553-90-1)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	125 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	9 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	> 10 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
formaldehyde ...% (50-00-0)	
LC50 - Fish [1]	6.7 mg/l Test organisms (species): Morone saxatilis
EC50 - Crustacea [1]	5.8 mg/l Test organisms (species): Daphnia pulex
ErC50 algae	4.89 – 6.61 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value)
NOEC (chronic)	≥ 6.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 48 mg/l Test organisms (species): Oryzias latipes Duration: '28 d'

Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.2. Persistence and degradability

Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Modified Paraffin (8002-74-2)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

hexamethylene diacrylate; hexane-1,6-diol diacrylate (13048-33-4)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Benzene-1,2,4,5-tetracarboxylic acid, compound with 4,5-dihydro-2-phenyl-1H-imidazole (1:1) (54553-90-1)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

formaldehyde ...% (50-00-0)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

Biochemical oxygen demand (BOD)	0.64
---------------------------------	------

Chemical oxygen demand (COD)	1.06 g O ₂ /g substance
------------------------------	------------------------------------

ThOD	1.068 g O ₂ /g substance
------	-------------------------------------

BOD (% of ThOD)	0.6 % ThOD
-----------------	------------

12.3. Bioaccumulative potential

formaldehyde ...% (50-00-0)

BCF - Fish [1]	< 1 (1 h, Flow-through system, Salt water, Weight of evidence)
----------------	--

Partition coefficient n-octanol/water (Log Pow)	0.35 (Calculated)
---	-------------------

Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
---------------------------	--

12.4. Mobility in soil

formaldehyde ...% (50-00-0)

Surface tension	73 mN/m (20 °C, Aqueous solution, 7.5 g/l)
-----------------	--

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.202 (log Koc, Calculated value)
--	-----------------------------------

Ecology - soil	Not applicable (gas). Toxic to flora.
----------------	---------------------------------------

12.5. Results of PBT and vPvB assessment

Component

Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	formaldehyde ...% (50-00-0) ⁽¹⁾
--	--

Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	formaldehyde ...% (50-00-0) ⁽¹⁾
---	--

⁽¹⁾ Substance(s) in concentration below 0.1 % and displayed on a voluntary basis

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
28.	formaldehyde ...%	Substances which are classified as carcinogen category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 1 or Appendix 2, respectively.
72.	formaldehyde ...%	The substances listed in column 1 of the Table in Appendix 12
77.	formaldehyde ...%	Formaldehyde and formaldehyde-releasing substances

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

Germany

- Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
- Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).
- Chemicals Prohibition Ordinance (ChemVerbotsV) : This product is subject to ChemVerbotsV Annex 1 Entry 1. Paragraph 1) Coated and uncoated wood-based materials (chipboard, blockboard, veneer panels, and fibreboard) may not be placed on the market if the equalizing concentration of formaldehyde in the air in a test room exceeds 0.1 ml / cbm (ppm). Paragraph 2) Furniture that contains wood-based materials that do not meet the requirements of Paragraph 1 may not be placed on the market. Paragraph 1 is also deemed to have been fulfilled if the furniture complies with the equalization concentration specified in paragraph 1 during a whole-body test. Paragraph 3) Detergents, cleaning agents and care products with a mass content of more than 0.2% formaldehyde may not be placed on the market.
- Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
	Version	Modified
	SDS EU format	Modified
	Revision date	Added
	Supersedes	Added

Abbreviations and acronyms:	
COD	Chemical oxygen demand (COD)
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS	Chemical Abstracts Service (division of the American Chemical Society)
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
CAS-No.	Chemical Abstract Service number
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
IOELV	Indicative Occupational Exposure Limit Value
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
N.O.S.	Not Otherwise Specified
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
Pow (log)	n-octanol/water partition coefficient

Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TRGS	Technical Rules for Hazardous Substances
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Data sources : Classification according to Regulation (EC) No. 1272/2008 [CLP]. ECHA (European Chemicals Agency). Supplier's safety documents.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Carc. 1B	Carcinogenicity, Category 1B
EUH208	Contains hexamethylene diacrylate; hexane-1,6-diol diacrylate (13048-33-4). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H412	Harmful to aquatic life with long lasting effects.
Muta. 2	Germ cell mutagenicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

The classification complies with : ATP 12

Glossmax/Glossmax Pro/Mattplus (MDF-based lacquer panels)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Safety Data Sheet (SDS), EU

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable